Max® Germany

Max Tools Quality Guarantee

1" Air Impact Wrench



Feature

- 1" impact wrench with ting+hole retainer
- Twin hammer clutch
- Front exhaust
- High power: 1400ft.lb/1898Nm
- Ideal for general maintenance
- Powerful motor and durable clutch
- Operator comfort andle swinng of only 90° to 110°

Code - RT5563

SPECIFICATIONS	
Square Drive	1"
Capacity Bolt Size	1-1/2"(M38mm)
Free Speed	4500rpm
Max Torque	1400ft.lb/1898N
Air Inlet	3/8"PT
Air Hose	3/4" I.D.
Air Consumption	8cfm
Net Weight	15.4lbs/7kgs

- Air Motor Features Quality Bearings, Ductile Steel End Plates and Carefully Finished Components to Ensure Smooth Running and Maximum Power. Combination Forward / Reverse and Speed Selector.
- Powerful 1" Impact Wrench with Twin Hammer Mechanism and Pressure Feed Lubrication System.
- Used in Automotive and Many Other Industries for Maintenance. • Heavy Duty • Weight：7.0 KG



1/2" Air Impact Wrench

- Heavy Duty
- Twin Hammer
- Front Exhaust

Code	RT5230
• Square Drive	1/2"
• Capacity Bolt Size	5/8" (M16)
• Free Speed	7500 rpm
• Max. Torque	480ft-lb (650N-m)
• Air Inlet	1/4" PT
• Air Hose	3/8" I.D
• Air Consumption	8 cfm
• Net Weight	3.50 lbs (2.60Kgs)



3/4" Air Impact Wrench

- Heavy Duty
- Twin Hammer
- Front Exhaust

Code	RT5550
• Square Drive	3/4"
• Capacity Bolt Size	1-1/4" (M28)
• Free Speed	4500 rpm
• Max. Torque	900ft-lb (1220N-m)
• Air Inlet	3/8" PT
• Air Hose	1/2" I.D.
• Air Consumption	12 cfm
• Net Weight	10.60 lbs (4.82Kgs)