Hand Tools



Float Switch - FPC-1



Technical parameters -

- Rated voltage / Frequency : 250V AC, 50Hz / 60Hz
- Rated current : 10 (4) A / 16 (4) A / 16 (8)
- A Degree of protection : IP 68
- Maximum operating temperature : 55 cable specifications : 3 × 0.75 mm^2

Mechanical Water Pump Control - MPC-2



Technical parameters -

- Pressure range : 15-175psi
- Pressure settings : 15-35 psi, 20-40 psi, 30-50 psi 40-60 psi, 50-80 psi, 95-125 psi 120-150 psi, 135-175 psi
- Rated current : 16 (10) A
- Rated voltage : 110V-240V
- Frequency : 50 / 60Hz
- Maximum ambient temperature : 55°C
- Protection class : IP54

Pressure Testing Pump - EPC-1



Technical parameters -

- Rated voltage : 220V-240V / 110V-120V
- Frequency : 50Hz / 60Hz
- The maximum current : 10A
- Maximum power : 1.1KW / 1.8KW
- Starting pressure setting : 1.5bar / 2.2bar
- The maximum working pressure : 10bar
- The interface thread : “G1”
- Protection class : IP65
- The maximum operating temperature : 60°C

Applications : Pump, Jet Pump, Garden Pump, Water Pump and other

Pressure Switch - EPC-5



Technical parameters -

- Rated voltage : 220V-240V / 110V-120V
- Frequency : 50Hz / 60Hz
- The maximum current : 10A
- Maximum power : 1.1KW / 1.8KW
- Starting pressure setting : 1.5bar / 2.2bar
- The maximum working pressure : 10bar
- The interface thread : “G1”
- Protection class : IP65
- The maximum operating temperature : 60°C

Applications : Pump, Jet Pump, Garden Pump, Water Pump and other

Mechanical Water Pump Control - MPC-1



Technical parameters -

- Rated voltage / Frequency : 230V / 50Hz. 115V / 60Hz
- Rated current / power : 12A / 2HP. 20A / 1.5HP
- Minimum on pressure : 20PSI
- Maximum disconnection pressure : 60PSI
- Pressure range : 20-40,30-50,40-60PSI
- Inlet Base : Metal